

## HTSK 100-09

Multi-function key safe



### Prime parameters

#### Size of the safe

External dimensions: 1250 mm × 700 mm × 550 mm

#### Resistance class and insurance

Security class I according to EN 1143-1

#### Colour

Choose your safe's standard colour or modify it

#### Key lock

Key lock

# Technical details

|                                     |  |
|-------------------------------------|--|
| External dimensions (H x W x D)     | 1250 mm x 700 mm x 550 mm  |
| Internal dimensions (H x W x D)     | 1111 mm x 564 mm x 380 mm  |
| Weight                              | 308 kg   |
| Capacity                            | 238 l  |
| Security class                      | I  |
| Limit of protected value – home     | to 65.000 €  |
| Limit of protected value – company  | to 20.000 €  |
| Standard lock                       | Key lock   |
| Size of the safe                    | Big  |
| Article number                      | HTSK 100-09  |
| Key hooks                           | 250  |
| Door opening direction              | right side   |
| Door thickness                      | 104 mm   |
| Door opening angle                  | 180°   |
| Door clearance dimensions           | 1096 x 546 mm  |
| Protruding door hinges/fitings      | 60 mm  |
| Lacquer/Colour                      | light grey RAL 7035  |
| Lock                                | VdS class I key lock (2 keys)  |
| Features of the lock                | 3-sided bolt locking system, the hinge area additionally secured by fixed pins   |
| More data on the body               | multi-walled, 62 mm  |
| Adapted for anchoring in the ground | yes  |
| Adapted for wall anchoring          | no   |
| Equipment                           | - an open, file binder-high (350 mm) compartment below, - above it an individually customisable, special key hook system on the side walls, rear wall and inside of the door, - horizontally and vertically adjustable key hooks, - length of the key hooks: 40 mm |