HTSK 100-11

Multi-function key safe



Prime parameters

Size of the safe

External dimensions: 1500 mm × 700 mm × 550 mm

Resistance class and insurance

Security class I according to EN 1143-1

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	1500 mm × 700 mm × 550 mm
Internal dimensions (H x W x D)	1361 mm × 564 mm × 380 mm
Weight	361 kg
Capacity	295 l
Security class	I
Limit of protected value – home	to 65.000 €
Limit of protected value – company	to 20.000 €
Standard lock	Key lock
Size of the safe	Big
Article number	HTSK 100-11
Key hooks	300
Door opening direction	right side
Door thickness	104 mm
Door opening angle	180°
Door clearance dimensions	1346 x 546 mm
Protruding door hinges/fittings	60 mm
Lacquer/Colour	light grey RAL 7035
Lock	VdS class I key lock (2 keys)
Features of the lock	3-sided bolt locking system, the hinge area additionally secured by fixed pins
More data on the body	multi-walled, 62 mm thick
Adapted for anchoring in the ground	yes
Adapted for wall anchoring	no
Equipment	- an open, file binder-high (350 mm) compartment below; - above it an individually customisable, special key hook system on the side walls, rear wall and inside of the door; - horizontally and vertically adjustable key hooks, - length of the key hooks: 40 mm