

## HTSK 130-06

Multi-function key safe



### Prime parameters

#### Size of the safe

External dimensions: 1050 mm × 700 mm × 550 mm

#### Resistance class and insurance

Security class I according to EN 1143-1

#### Colour

Choose your safe's standard colour or modify it

#### Key lock

Key lock

# Technical details

External dimensions (H x W x D)	1050 mm x 700 mm x 550 mm
Internal dimensions (H x W x D)	900 mm x 535 mm x 350 mm
Weight	300 kg
Capacity	168 l
Security class	I
Limit of protected value – home	to 65.000 €
Limit of protected value – company	to 20.000 €
Standard lock	Key lock
Size of the safe	Medium
Article number	HTSK 130-06
Adjustable shelves	--
Key hooks	135
Door opening direction	right side
Door thickness	135 mm
Door opening angle	180°
Door clearance dimensions	852 x 482 mm
Protruding door hinges/fitings	60 mm
Lacquer/Colour	light grey RAL 7035
Lock	VdS class I key lock (2 keys)
Features of the lock	multi-sided bolt locking system
More data on the body	- multi-walled on all sides, - fire-retardant insulating mantle according to DIN 4102, - with wrap-around fire insulation
Adapted for anchoring in the ground	yes
Adapted for wall anchoring	no
Equipment	- 3 key hook rails with 8 hooks each on the rear wall and on the inside of the door with a total of 48 special key hooks, - 3 hook rails with 7 hooks each on the left and right side walls for a total of 42 special key hooks, - 90 special key hooks in total, - the hook slats can be set at different heights (infinitely variable), - a file binder-high lockable inner compartment in the bottom part of the safe