HTSK 200-06

Multi-function key safe



Prime parameters

Size of the safe

External dimensions: 1006 mm × 636 mm × 510 mm

Resistance class and insurance

Security class II according to EN 1143-1

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	1006 mm × 636 mm × 510 mm
Internal dimensions (H x W x D)	867 mm × 520 mm × 344 mm
Weight	486 kg
Capacity	159 l
Security class	II
Limit of protected value – home	to 100.000 €
Limit of protected value – company	to 50.000 €
Standard lock	Key lock
Size of the safe	Medium
Article number	HTSK 200-06
Adjustable shelves	--
Key hooks	200
Door opening direction	right side
Door thickness	109 mm
Door opening angle	180°
Door clearance dimensions	872 x 502 mm
Protruding door hinges/fittings	60 mm
Lacquer/Colour	light grey RAL 7035
Lock	high security key lock (2 keys)
Features of the lock	3-sided bolt locking system, the hinge area additionally secured by fixed pins
More data on the body	- multi-walled, - with high-strength special concrete filling, - 52 mm thick
Adapted for anchoring in the ground	yes
Adapted for wall anchoring	no
Equipment	- one, file binder-height open compartment (350 mm) below; - above it an individually customisable, special key hook system on the side walls, rear wall and inside of the door; - individually adjustable key hooks in terms of both height and lateral position, - length of the key hooks: 40 mm