

## HTSK 200-08

Multi-function key safe



### Prime parameters

#### Size of the safe

External dimensions: 1206 mm × 636 mm × 510 mm

#### Resistance class and insurance

Security class II according to EN 1143-1

#### Colour

Choose your safe's standard colour or modify it

#### Key lock

Key lock

# Technical details

External dimensions (H x W x D)	1206 mm x 636 mm x 510 mm
Internal dimensions (H x W x D)	1087 mm x 520 mm x 344 mm
Weight	565 kg
Capacity	194 l
Security class	II
Limit of protected value – home	to 100.000 €
Limit of protected value – company	to 50.000 €
Standard lock	Key lock
Size of the safe	Big
Article number	HTSK 200-08
Adjustable shelves	--
Key hooks	250
Door opening direction	right side
Door thickness	109 mm
Door opening angle	180°
Door clearance dimensions	1072 x 502 mm
Protruding door hinges/fitings	60 mm
Lacquer/Colour	light grey RAL 7035
Lock	high security key lock (2 keys)
Features of the lock	3-sided bolt locking system, the hinge area additionally secured by fixed pins
More data on the body	- multi-walled, - with high-strength special concrete filling, - 52 mm thick
Adapted for anchoring in the ground	yes
Adapted for wall anchoring	no
Equipment	- one, file binder-height open compartment (350 mm) below; - above it an individually customisable, special key hook system on the side walls, rear wall and inside of the door; - individually adjustable key hooks in terms of both height and lateral position, - length of the key hooks: 40 mm