# HTSK 200-11

Multi-function key safe



## Prime parameters

### Size of the safe

External dimensions: 1500 mm × 700 mm × 550 mm

### Resistance class and insurance

Security class II according to EN 1143-1

### Colour

Choose your safe's standard colour or modify it

### Key lock

Key lock

# Technical details

| | |
|---|---|
| External dimensions (H x W x D) | 1500 mm × 700 mm × 550 mm |
| Internal dimensions (H x W x D) | 1381 mm × 584 mm × 384 mm |
| Weight | 766 kg |
| Capacity | 310 l |
| Security class | II |
| Limit of protected value – home | to 100.000 € |
| Limit of protected value – company | to 50.000 € |
| Standard lock | Key lock |
| Size of the safe | Big |
| Article number | HTSK 200-11 |
| Adjustable shelves | -- |
| Key hooks | 300 |
| Door opening direction | right side |
| Door thickness | 109 mm |
| Door opening angle | 180° |
| Door clearance dimensions | 1366 x 566 mm |
| Protruding door hinges/fittings | 60 mm |
| Lacquer/Colour | light grey RAL 7035 |
| Lock | high security key lock (2 keys) |
| Features of the lock | 3-sided bolt locking system, the hinge area additionally secured by fixed pins |
| More data on the body | - multi-walled, - with high-strength special concrete filling, - 52 mm thick |
| Adapted for anchoring in the ground | yes |
| Adapted for wall anchoring | no |
| Equipment | - one, file binder-height open compartment (350 mm) below; - above it an individually customisable, special key hook system on the side walls, rear wall and inside of the door; - individually adjustable key hooks in terms of both height and lateral position, - length of the key hooks: 40 mm |