HTSK 230-06

Multi-function key safe



Prime parameters

Size of the safe

External dimensions: 1000 mm × 600 mm × 550 mm

Resistance class and insurance

Security class II according to EN 1143-1

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	1000 mm × 600 mm × 550 mm
Internal dimensions (H x W x D)	880 mm × 465 mm × 345 mm
Weight	420 kg
Capacity	141 l
Security class	II
Limit of protected value – home	to 65.000 €
Limit of protected value – company	to 20.000 €
Standard lock	Key lock
Size of the safe	Medium
Article number	HTSK 230-06
Adjustable shelves	--
Key hooks	126
Door opening direction	right side
Door thickness	135 mm
Door opening angle	180°
Door clearance dimensions	852 x 482 mm
Protruding door hinges/fittings	60 mm
Lacquer/Colour	light grey RAL 7035
Lock	VdS class I key lock (2 keys)
Features of the lock	multi-sided bolt locking system
More data on the body	- allround multi-walled, - fire insulation mantle acc. to DIN 4102, fire safety strip around the door
Adapted for anchoring in the ground	yes
Adapted for wall anchoring	no
Equipment	- 3 key hook rails each with 7 hooks on the rear wall and on the inside of the door with a total of 42 special key hooks, - 3 hook rails with 7 hooks each on the left and right side walls for a total of 42 special key hooks, - 84 special key hooks in total, - rails with key hooks can be set at different heights (stepless), - a lockable, file binder high, inner compartment at the bottom of the safe