# K 104-04/2

**Business safe**



## Prime parameters

### Size of the safe

External dimensions: 1200 mm × 640 mm × 550 mm

### Colour

Choose your safe's standard colour or modify it

### Key lock

Key lock

# Technical details

| | |
|---|---|
| External dimensions (H x W x D) | 1200 mm × 640 mm × 550 mm |
| Internal dimensions (H x W x D) | 1050 mm × 475 mm × 410 mm |
| Weight | 200 kg |
| Capacity | 204 l |
| Standard lock | Key lock |
| Size of the safe | Big |
| Article number | K 104-04/2 |
| Adjustable shelves | 2 |
| File binders | 15 |
| Door opening angle | 180° |
| Door opening direction | right side |
| Door thickness | 75 mm |
| Door clearance dimensions | 1050 x 475 mm |
| Protruding door hinges/fittings | 50 mm |
| Lacquer/Colour | light grey RAL 7035 |
| Features of the lock | - 3-sided bolt locking system, additional fixed pins on the hinge side, - special armour plate to protect the lock against against drilling and milling |
| Lock | VdS class I key lock (2 keys included) |
| More data on the body | double-wall, fire insulation, fire safety strip in the door frame |
| More data on the door | double-walled, 6 mm thick plate, fire insulation |
| Adapted for anchoring in the ground | tak |
| Adapted for wall anchoring | yes |