

## PDE 1276 SL

Multi-function key safe



### Prime parameters

#### Size of the safe

External dimensions: 1200 mm × 700 mm × 550 mm

#### Resistance class and insurance

Security class I according to EN 1143-1

#### Colour

Choose your safe's standard colour or modify it

#### Key lock

Key lock

# Technical details

External dimensions (H x W x D)	1200 mm x 700 mm x 550 mm
Internal dimensions (H x W x D)	1050 mm x 535 mm x 350 mm
Weight	340 kg
Capacity	197 l
Security class	I
Limit of protected value – home	to 65.000 €
Limit of protected value – company	to 20.000 €
Standard lock	Key lock
Size of the safe	Big
Article number	PDE 1276 SL
Adjustable shelves	--
Key hooks	168
Adjustable hook slats	yes
Door opening direction	right side
Door thickness	125 mm
Door opening angle	180°
Door clearance dimensions	1010 x 510 mm
Protruding door hinges/fittings	50 mm
Lacquer/Colour	light grey RAL 7035
Lock	VdS class I key lock (2 keys)
Features of the lock	- 3-sided bolt locking system of round steel pins with a diameter of 35 mm , - additional fixed pins at the hinge side, emergency bolt locking, - lock and bolt cover
More data on the body	- triple-walled with integrated reinforcement, - fire insulation mantle acc. to DIN 4102, fire safety strip
More data on the door	four-walled
Adapted for anchoring in the ground	yes
Adapted for wall anchoring	no

---

Equipment

- 3 individually removable key walls on telescopic pullouts at the top, - 8×7 key hook rails per wall, hooks spaced 45 mm apart, rails unnumbered, no colour designation, - rails with key hooks can be set at different heights, - 130 mm height distance from the middle of one hook rail to the middle of the other one, - beneath an open, folder-height compartment.

---