

PDE 1576

Burglar-proof safe



Prime parameters

Size of the safe

External dimensions: 1500 mm × 750 mm × 550 mm

Resistance class and insurance

Security class I according to EN 1143-1

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

| | |
|-------------------------------------|---|
| External dimensions (H x W x D) | 1500 mm x 750 mm x 550 mm |
| Internal dimensions (H x W x D) | 1350 mm x 585 mm x 350 mm |
| Weight | 300 kg |
| Capacity | 276 l |
| Security class | I |
| Limit of protected value – home | to 65.000 € |
| Limit of protected value – company | to 20.000 € |
| Standard lock | Key lock |
| Size of the safe | Big |
| Article number | PDE 1576 |
| Adjustable shelves | 3 |
| File binders | 28 |
| Anti-burglary protection standard | EN 1143-1 |
| Certification body | VdS |
| Door opening angle | 180° |
| Door opening direction | right side |
| Door thickness | 125 mm |
| Door clearance dimensions | 1310 x 560 mm |
| Protruding door hinges/fittings | 50 mm |
| Lacquer/Colour | light grey RAL 7035 |
| Features of the lock | - 3-sided bolt locking system with round steel pins of 35 mm diameter, - in addition, fixed pins on the hinge side, emergency locking system, - lock and bolt cover |
| Lock | VdS class I key lock (2 keys included) |
| More data on the body | - triple-walled with integrated reinforcements, - fire-retardant insulating mantle according to DIN 4102, - fire safety strip |
| More data on the door | four-walled |
| Adapted for anchoring in the ground | tak |