PDE 676/3

Burglar-proof safe



Prime parameters

Size of the safe

External dimensions: 650 mm × 700 mm × 550 mm

Resistance class and insurance

Security class I according to EN 1143-1

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	650 mm × 700 mm × 550 mm
Internal dimensions (H x W x D)	500 mm × 535 mm × 350 mm
Weight	300 kg
Capacity	94 l
Security class	I
Limit of protected value – home	to 65.000 €
Limit of protected value – company	to 20.000 €
Standard lock	Key lock
Size of the safe	Medium
Article number	PDE 676/3
Adjustable shelves	1
File binders	6
Anti-burglary protection standard	EN 1143-1
Certification body	VdS
Door opening angle	180°
Door opening direction	right side
Door thickness	125 mm
Door clearance dimensions	460 x 510 mm
Protruding door hinges/fittings	50 mm
Lacquer/Colour	light grey RAL 7035
Features of the lock	- 3-sided bolt locking system with round steel pins of 35 mm diameter, - in addition, fixed pins on the hinge side, emergency locking system, - lock and bolt cover
Lock	VdS class I key lock (2 keys included)
More data on the body	- triple-walled with integrated reinforcements, - fire-retardant insulating mantle according to DIN 4102, - fire safety strip
More data on the door	four-walled
Adapted for anchoring in the ground	tak