

## PDII 1065

Burglar-proof safe



### Prime parameters

#### Size of the safe

External dimensions: 1000 mm × 600 mm × 550 mm

#### Resistance class and insurance

Security class II according to EN 1143-1

#### Colour

Choose your safe's standard colour or modify it

#### Key lock

Key lock

# Technical details

|                                     |   |
|-------------------------------------|---|
| External dimensions (H x W x D)     | 1000 mm x 600 mm x 550 mm   |
| Internal dimensions (H x W x D)     | 880 mm x 465 mm x 345 mm  |
| Weight                              | 420 kg  |
| Capacity                            | 141 l   |
| Security class                      | II  |
| Limit of protected value – home     | to 100.000 €  |
| Limit of protected value – company  | to 50.000 €   |
| Standard lock                       | Key lock  |
| Size of the safe                    | Medium  |
| Article number                      | PDII 1065   |
| Adjustable shelves                  | 2   |
| File binders                        | 10  |
| Anti-burglary protection standard   | EN 1143-1   |
| Certification body                  | VdS   |
| Door opening angle                  | 170°  |
| Door opening direction              | right side  |
| Door thickness                      | 140 mm  |
| Door clearance dimensions           | 835 x 435 mm  |
| Protruding door hinges/fittings     | 50 mm   |
| Lacquer/Colour                      | light grey RAL 7035   |
| Features of the lock                | - 3-sided bolt locking system with round steel pins of 35 mm diameter, - in addition, fixed pins on the hinge side, emergency locking system, - lock and bolt cover |
| Lock                                | VdS class I key lock (2 keys included)  |
| More data on the body               | - triple-walled on all sides, - special concrete filling to protect from fire and break-in  |
| More data on the door               | triple-walled, armour to protect against against drilling, milling and cutting; concrete filling like in the body   |
| Adapted for anchoring in the ground | tak   |