

## PDII 1065

Burglar-proof safe



### Prime parameters

#### Size of the safe

External dimensions: 1000 mm × 600 mm × 550 mm

#### Resistance class and insurance

Security class II according to EN 1143-1

#### Colour

Choose your safe's standard colour or modify it

#### Key lock

Key lock

# Technical details

External dimensions (H x W x D)	1000 mm x 600 mm x 550 mm
Internal dimensions (H x W x D)	880 mm x 465 mm x 345 mm
Weight	420 kg
Capacity	141 l
Security class	II
Limit of protected value – home	to 100.000 €
Limit of protected value – company	to 50.000 €
Standard lock	Key lock
Size of the safe	Medium
Article number	PDII 1065
Adjustable shelves	2
File binders	10
Anti-burglary protection standard	EN 1143-1
Certification body	VdS
Door opening angle	170°
Door opening direction	right side
Door thickness	140 mm
Door clearance dimensions	835 x 435 mm
Protruding door hinges/fittings	50 mm
Lacquer/Colour	light grey RAL 7035
Features of the lock	- 3-sided bolt locking system with round steel pins of 35 mm diameter, - in addition, fixed pins on the hinge side, emergency locking system, - lock and bolt cover
Lock	VdS class I key lock (2 keys included)
More data on the body	- triple-walled on all sides, - special concrete filling to protect from fire and break-in
More data on the door	triple-walled, armour to protect against against drilling, milling and cutting; concrete filling like in the body
Adapted for anchoring in the ground	tak