

S 102-06

Wall safe



Prime parameters

Size of the safe

External dimensions: 500 mm × 510 mm × 383 mm

Resistance class and insurance

Security class I according to EN 1143-1

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

| | |
|-------------------------------------|---|
| External dimensions (H x W x D) | 500 mm x 510 mm x 383 mm |
| Internal dimensions (H x W x D) | 406 mm x 400 mm x 295 mm |
| Weight | 55 kg |
| Capacity | 48 l |
| Security class | I |
| Limit of protected value – home | to 65.000 € |
| Limit of protected value – company | to 20.000 € |
| Standard lock | Key lock |
| Size of the safe | Small |
| Article number | S 102-06 |
| Adjustable shelves | 1 |
| File binders | 5 |
| Certification body | VdS |
| Anti-burglary protection standard | EN 1143-1/I |
| Door opening direction | right side |
| Door opening angle | 90° |
| Door thickness | 80 mm |
| Door clearance dimensions | 406 x 310 mm |
| Lacquer/Colour | light grey RAL 7035 |
| Lock | VdS class I key lock (2 keys) |
| Features of the lock | - 4-sided bolt locking system, fixed pins on hinge side, - pins with 35 mm diameter, - locking mechanism protected by an emergency locking system and armoured plates; armoured plates also around the lock |
| More data on the body | made of Siemens-Martin steel |
| More data on the door | triple-walled, 12 mm thick steel plate, fire insulation acc. to the German standard DIN 4102 |
| Adapted for anchoring in the ground | no |