HT ES 120

Key management system

Prime parameters

Size of the safe

External dimensions: 680 mm × 980 mm × 190 mm

Colour

Choose your safe's standard colour or modify it

Electronic lock

Electronic lock

Technical details

External dimensions (H x W x D)	680 mm × 980 mm × 190 mm
Internal dimensions (H x W x D)	mm × mm × mm
Weight	58 kg
Standard lock	Electronic lock
Size of the safe	Medium
Article number	HT ES 120
Adjustable hook slats	no
Door opening direction	left side
Lacquer/Colour	anthracite RAL 7016, door – stainless steel
Lock	electromagnetic
Features of the lock	IP 65 alphanumeric keypad available
More data on the body	steel, 1,5 mm thick (IP 41)
More data on the door	made of stainless steel (polycarbonate door optionally available)
Adapted for anchoring in the ground	no
Adapted for wall anchoring	yes
Equipment	- 120 key slots, - slots with key lock, slots for bunches of keys, - power connector: 100-240 V, - emergency power supply: 2 x 12 V battery, - more than 20 different alarms available, alarm can be switched to a master alarm system. Features: - access rights for up to 1000 users, - individual assignment of rights to open the depository and retrieve specific keys, - integrated data memory (up to 25,000 records).