

SP 1420

Drawer safe



Prime parameters

Size of the safe

External dimensions: 1420 mm × 640 mm × 580 mm

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

| | |
|-------------------------------------|---|
| External dimensions (H x W x D) | 1420 mm x 640 mm x 580 mm |
| Internal dimensions (H x W x D) | 1050 mm x 475 mm x 410 mm |
| Weight | 300 kg |
| Capacity | 204 l |
| Standard lock | Key lock |
| Size of the safe | Big |
| Article number | SP 1420 |
| Drop system | drawer |
| Adjustable shelves | 1 |
| File binders | 0 |
| Anti-burglary protection standard | EN 14450 |
| Lacquer/Colour | light grey RAL 7035 |
| Lock | high security key lock at the door and the drawer (2 keys for each lock) |
| Door opening direction | right side |
| Door opening angle | 90° |
| Door thickness | 80 mm |
| Protruding door hinges/fittings | 12 mm |
| Features of the lock | locking from several sides, lock area protected against drilling |
| More data on the body | - double-wall 52 mm, - wrap-around fire protection strip, - high quality fire insulation acc. to the German standard DIN 4102 |
| More data on the door | double-wall, fire insulation as in the body |
| Adapted for wall anchoring | no |
| Adapted for anchoring in the ground | yes |
| Interior fittings | drawer on telescopic rails, an 300 mm high internal safe as deposit compartment |