


HTIV 445-03

Safe for valuables

**Przepraszam,
muszę się
sfotografować.**



Prime parameters

Size of the safe

External dimensions: 1190 mm × 666 mm × 548 mm

Resistance class and insurance

Security class IV according to EN 1143-1

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	1190 mm x 666 mm x 548 mm
Internal dimensions (H x W x D)	1082 mm x 560 mm x 350 mm
Weight	560 kg
Capacity	212 l
Security class	IV
Limit of protected value – home	to 400.000 €
Limit of protected value – company	to 150.000 €
Standard lock	Key lock
Size of the safe	Big
Article number	HTIV 445-03
Adjustable shelves	1
Anti-burglary protection standard	EN 1143-1
Fire resistance	IBS-tested fire and smoke protection through Thermodur seals in the door leaf
Certification body	VdS
Door opening angle	90°
Door opening direction	right side
Door clearance dimensions	997 x 480 mm
Protruding door hinges/fittings	60 mm
Lacquer/Colour	light grey RAL 7035
Lock	high security key lock (2 keys included) + mechanical combination lock
Features of the lock	3-sided bolt locking system with strong pins of 50 mm diameter
More data on the body	- lighter weight due to armouring: shell made of Siemens-Martin steel, filled with Hartsinter stones and bicomponent material, - Hartsinter hardness grade 9, melting point 2000 °C, - Nervoform protection system in the event of heat exposure, - protection against bursting and cutting with a torch
Adapted for anchoring in the ground	yes
Adapted for wall anchoring	no
Equipment	preparation for connection of an alarm system