

## HTSO 36 Set of bank lockers



### Prime parameters

#### Size of the safe

External dimensions: 1910 mm × 1020 mm × 430 mm

#### Colour

Choose your safe's standard colour or modify it

#### Key lock

Key lock

# Technical details

|                                     |  |
|-------------------------------------|--|
| External dimensions (H x W x D)     | 1910 mm x 1020 mm x 430 mm   |
| Internal dimensions (H x W x D)     | mm x mm x mm   |
| Weight                              | 420 kg   |
| Standard lock                       | Key lock   |
| Size of the safe                    | Big  |
| Article number                      | HTSO 36  |
| Door opening angle                  | 90°  |
| Door opening direction              | right side   |
| Door thickness                      | 3 mm   |
| Lacquer/Colour                      | corpus – anthracite RAL 7016, door – stainless steel   |
| Features of the lock                | - German certificate VDS DIN EN1303, - mechanical central locking of each block, - locking of the whole set with a cylindrical lock and a security card  |
| Lock                                | key lock   |
| More data on the body               | 2 mm thick   |
| Adapted for anchoring in the ground | tak  |
| Equipment                           | - a cassette for placing a deposit for every locker up to a height of 200 mm, - numbered lockers Configuration (left side from top to bottom): left block: 3 lockers 50 mm high, 4 lockers 75 mm high, 3 lockers 100 mm high, 1 locker 150 mm high, 1 locker 200 mm high, 1 locker 300 mm high, 1 locker 400 mm high central block: 16 lockers 75 mm high, 2 lockers 150 mm high, 1 locker 300 mm high right block: 4 lockers 300 mm high, 1 locker 600 mm high Option: electronic lock instead of key lock in the lockers |