HBD1-1010

Blast proof armoured hatch door



Prime parameters

Size of the safe

External dimensions: 1400 mm × 1400 mm × 245 mm

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	1400 mm × 1400 mm × 245 mm
Internal dimensions (H x W x D)	mm × mm × mm
Weight	857 kg
Standard lock	Key lock
Article number	HBD1-1010
Anti-burglary protection standard	NO-13-A247-2019
Fire resistance	in acc. with PN-EN 1363-1 and PN-EN 1634-1 standards
Door opening direction	right side
Lock	2 cylindric key locks
Door clearance dimensions	1000 x 1000 mm (W x Sz)
Door opening angle	180°
Features of the lock	- 3-sided central bolt work, pins of 40 mm diameter, - two emergency mechanical locks, - both locking systems operable from the outside and inside
Lacquer/Colour	light grey RAL 7035, primer resisting corrosion
Door thickness	245 mm
Door properties	- high efficient construction of steel and reinforced concrete, - a concrete slab inside, thickness: 100 mm, - resistant to an explosion of 9 bar and to a reflected pressure of 21 bar
Equipment	- two sturdy safe type hinges, - fully automatic opening and closing of doors and locks (in the event of manual operation of the mechanism or the occurrence of a specific event)