

HBD2-5050

Blast proof armoured door, 2-wings



Prime parameters

Size of the safe

External dimensions: 5600 mm × 5800 mm × 400 mm

Colour

Choose your safe's standard colour or modify it

Electronic lock

Electronic lock

Technical details

External dimensions (H x W x D)	5600 mm x 5800 mm x 400 mm
Internal dimensions (H x W x D)	mm x mm x mm
Weight	23500 kg
Standard lock	Electronic lock
Article number	HBD2-5050
Anti-burglary protection standard	NO-13-A247-2019
Fire resistance	in acc. with PN-EN 1363-1 and PN-EN 1634-1 standards
Door opening direction	both sides
Lock	electronic
Door clearance dimensions	5000 x 5000 mm (W x Sz)
Door opening angle	180°
Features of the lock	- 3-sided central bolt work, pins of 80 mm diameter, - two emergency mechanical locks, - both locking systems operable from the outside and inside
Lacquer/Colour	light grey RAL 7035, primer resisting corrosion
Door thickness	400 mm
Door properties	- the weight of steel alone: 11.150 kg, - high efficient construction of steel and reinforced concrete, - a concrete slab inside, thickness: 300 mm, - resistant to an explosion of 9 bar and to a reflected pressure of 28 bar
Equipment	- two sturdy safe type hinges, - removable rubber seals around the perimeter of the door, weather-resistant, - fully automatic opening and closing of doors and locks (in the event of manual operation of the mechanism or the occurrence of a specific event), - numerous additional options available, e.g. removable hinges, padlock closure from the outside, hatch door