

## HT Server

Server safe



### Prime parameters

#### Size of the safe

External dimensions: 1180 mm × 755 mm × 1070 mm

#### Resistance class and insurance

Security class I according to EN 1143-1

#### Colour

Choose your safe's standard colour or modify it

#### Key lock

Key lock

# Technical details

External dimensions (H x W x D)	1180 mm x 755 mm x 1070 mm
Internal dimensions (H x W x D)	mm x mm x mm
Weight	495 kg
Security class	I
Limit of protected value – home	to 5.000 €
Limit of protected value – company	to 2.500 €
Standard lock	Key lock
Size of the safe	Big
Article number	HT Server
Door opening angle	180°
Anti-burglary protection standard	PN-EN 1143-1
Door opening direction	right side
Lacquer/Colour	ligh grey RAL 7035
More data on the body	server chassis certified to the NSA 94-106 guideline
Equipment	- approved in according to ECB•S R16 (ECB•S Guideline for the certification of IT safes), - place for 15 server elements (15 x 19" shelves), - speed-controlled fans for cooling the safe interior, - temperature sensor, - a shielded server cabinet as insert can be produced. Specification: • certified in according to NSA 94-106 / EN 50147-1, • fan data 220-240 V AC, 50/60 Hz, 20/19 WATT, 43/48 dB (A), • installed three fans, 432 m <sup>3</sup> /h / 534 m <sup>3</sup> /h, • the cable glands have a radius of 10 cm for optimal routing of the fiberoptic cables.