

Reinforced portable shelter HWS 40



Prime parameters

Size of the safe

External dimensions: 2533 mm × 2490 mm × 12140 mm

Resistance class and insurance

Security class V according to EN 1143-1

Colour

Choose your safe's standard colour or modify it

Electronic lock

Electronic lock

Technical details

External dimensions (H x W x D)	2533 mm x 2490 mm x 12140 mm
Internal dimensions (H x W x D)	mm x mm x mm
Weight	26300 kg
Security class	V
Standard lock	Electronic lock
Size of the safe	Big
Article number	HWS 40
Fire resistance	EI 120
Door opening direction	right side
Lacquer/Colour	light grey RAL 7035
More data on the body	camouflage variants: urban, forest, desert
Equipment	<p>– space for approx. 40 people (platoon), – integrated systems: passive protection, life support (AC, WC), life-saving medical equipment, GP, CIS, COP, active protection systems, – additional systems: reconnaissance and observation, kinetic and non-kinetic weapons, satellite communication (SatCom), friend or foe identification (IFF), protection against chemical, biological, radiological and nuclear weapons (CBRN), – can be constructed as a stationary shelter, buried in the ground, – can be transported by a multilift wheeled vehicle. Further safety parameters: – bullet resistance: FB7-NSV, – blast resistance: 7 bar, tested according to ATP-3.12.1.8, 21 bar according to FEM analysis, – protection against drones. Mobile shelter variants: – protective shelter, – combat shelter, – command and control station, – communications and information systems station, – medical aid station, – ammunition or small arms storage, – equipment storage.</p>